



Part Number:

Description

OMNTEC sensors are most known for their ease of installation, reliability, cost effectiveness and their ability to be tested remotely. Bright Eye sensors (BX-series) are self diagnostic, and programmed to identify themselves and their location, providing the user with critical information.

Each sensor can recognize its unique serial number, part number and function. It accomplishes this via an internal microprocessor that enables it to distinguish itself from the other sensors on the system. This information is then relayed back to the OEL8000III controller, eliminating the need to guess where a leak condition is occurring.


Built with four wire buss technology, up to 22 Bright Eye (BX-series) sensors can be networked along a common cable. (A total of 44 Bright Eye sensors can be used with the OEL8000III.) This eliminates the need to run separate lines for every sensor, which results in fewer conduits, and a quicker, less expensive and easier installation. In addition, systems already installed can be easily retrofitted without the need to run new cable.

A major feature of these sensors is that they can be tested from a remote location with the press of a single button, which has been third party certified.


OMNTEC BX-Series non-distinguishing sensors employ proven optic technology for leak detection applications. An internal microprocessor enables these sensors to be self diagnostic and self identifying. Each sensor can recognize its serial number, part number and function. This allows the controller to differentiate one sensor from another on the network and relay critical information to the user.

The BX-LS non-distinguishing sensor was designed to accommodate a variety of applications. With its convenient size and ability to detect liquids at any angle, the BX-LS sensor is the ideal sensor for sumps, dispenser pans, containment areas and annular spaces of double-wall steel tanks.


Principles of Operation



Dry Condition



Wet Condition



BX-Series Sensors Specifications

Power Consumption:	12 VDC @ 1.4 mA
Sensor Cable:	Shielded 22 AWG with drain wire (OMNTEC EC-4) Maximum length 2,000 feet
Principles of Operation:	
Normal Condition:	Normally closed beam of light
Alarm Condition:	Normally closed beam of light opens (refracts)
Water Condition (BX-PDS, BX-PDWS and BX-PDWF only):	Conductivity electrode
Response Time:	Immediate
Operating Temperature:	-15 to 140° F
Compatible Controllers:	OEL8000II and OEL8000III
Approvals:	UL Listed, CUL Listed, CE Listed

Content subject to change without notice, verify with manufacturer.

Features

- Self identifying by part number, serial number and function
- Self diagnostic
- Easily installed
- Minimal conduit needed
- Minimal programming required
- Product distinguishing or liquid only detection
- Easily tested without removal
- Corrosion resistant
- Not affected by hydrocarbon vapors or condensation
- Intrinsically safe
- Detects liquids at any angle
- No moving parts
- Modified sensors available
- Cost effective
- Third party certified
- UL listed, CUL listed, CE listed